



Vehicle
Certification
Agency



Maritime &
Coastguard
Agency



Department
for Transport



VCA Dangerous Goods Office
Cleeve Road, Leatherhead
Surrey, KT22 7NF, UK
T +44 (0)1372 226110
F +44 (0)1372 226116
E dgenquiries@vca.gov.uk
www.dft.gov.uk/vca

CERTIFICATE OF PACKAGING PERFORMANCE

Issued on behalf of the Department for Transport, Civil Aviation Authority and the Maritime and Coastguard Agency by the VCA Dangerous Goods Office

Certificate serial number: **6867**

NOT TRANSFERABLE

Application No.: **9179**

Issue number and date: **01 25/07/2018**

Issued to: **EGBERT H TAYLOR & COMPANY LTD**
Oak Park
Ryelands Lane
Elmley Lovett
Worcestershire
WR9 0QZ

Packaging type: **11A** Description:
Rigid, steel intermediate bulk container
for solids discharged by gravity

Capacity: **790 litres**

Tare: **173**

No of Entry Points: **2**

Top Lift: **Yes**

Contents: **Tested with shot blast material for solids or articles**

790 litre galvanised mild steel rectangular shaped, stackable IBC with full aperture hinged lid and fitted with two-way entry forkliftable base. Top lift assemblies 4mm thick fitted at each corner and 5mm thick corner stacking assemblies. The IBC is constructed from 2mm thick, galvanised mild steel panels, welded to form a rectangular shaped IBC with radiused corners and 2mm thick base panel incorporating 2mm thick foot plate sections. Closure of the hinged lid is by way of two pull over centre toggle catches. Bottom lift facilitated with 2mm thick fork channels with 200mm internal width.

Special Notes: For articles with a maximum bulk density of 1.72g/cc and a particle size of 440 microns. Optional louvred panels are available for waste aerosols as content. Container commercial ID; Wastesafe 800

It is certified that a sample of the design type described above has been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.5 and appropriate paragraphs from 6.5.6.4 to 6.5.6.9 and successfully met the criteria. IBCs of the design type tested may bear the marking:



** ** To be replaced by the month and the last two digits of the year of manufacture

THE TEST REPORT(S) AND ITS APPENDICES ARE AN INTEGRAL PART OF THIS DOCUMENT

The additional marking specified in 6.5.2.2 must be applied to each serially produced IBC.

When permitted by national or modal regulations, IBCs of the design type described may be used for Solids.

DROP HEIGHT (m)	1.8	packing group	bulk density (d)	gross mass (kg)
STACK HEIGHT	2 High	I	1.72	1390
INTERNAL PRESSURE (kPa)	-	II	1.72	1390
LEAKPROOFNESS (kPa)	-	III	1.72	1390

Revalidation due by: 31/12/2023

For further details see www.vca.gov.uk

Signed:

Keith F B White, Principal Consultant VCA DGO